



sidekick

The compact, by-your-side, all-in-one scanner.



sidekick¹²⁰⁰

sidekick^{1400u}

Everything you need for desktop document management, all in one box.

Scanning Mode	Duplex				
Scanning Speed Letter Size Portrait	Binary 200 dpi	Simplex 23 ppm (pages per minute) Duplex 42 ipm (images per minute)		Simplex 43 ppm (pages per minute) Duplex 76 ipm (images per minute)	
	Color 200 dpi	Simplex 8 ppm Duplex 14 ipm		Simplex 14 ppm Duplex 24 ipm	
Resolution	100-600 dpi, Color (with VRS) 100-400 dpi Optical: 600 dpi				
Output Options	Bitonal, Grayscale (8 bit), and Color (24 bit)				
Image Enhancement	 VRS 4.2 Professional features include Auto Cropping, Deskew, Auto Brightness, Advanced Clarity, Auto Color Detect, Auto Orientation, Bar Code Detection and Blank Page Deletion				
Document Size	2.0 x 2.8 in. (50.8 x 70 mm) to 8.5 x 14 in. (216 x 356 mm), Up to 8.5 x 25 in. (216 x 635mm)				
Paper Thickness	Single Paper Feeding: 2.0 to 5.9 mils (0.05 to 0.15 mm) Continuous Paper Feeding: 2.36 to 5.9 mils (0.06 to 0.15 mm) Note: 1 mil = 1/1000 in.				
Paper Weight	Single Paper Feeding: 10.7 to 33.9 lbs. Continuous Paper Feeding: 13.3 to 33.9 lbs.				
Interface	 USB 2.0 (cable included) and SCSI III (50 pin)		 USB 2.0 (cable included)		
Multifeed Detection	Length))) Ultrasonic		
Feeder Capacity	120 Sheets				
Scanner Size	14 x 12.5 x 9.25 in. (35.5 x 32 x 24.1 cm) With Tray Extended: 14 x 19.75 x 10.6 in. (35.5 x 50 x 27 cm)				
Scanner Weight	18.7 lbs (8.5 kg)		20.1 lbs (9.1 kg)		
Power Requirements	AC 100-120 V 50/60 Hz	AC 220-240 V 50/60 Hz	AC 100-120 V 50/60 Hz	AC 220-240 V 50/60 Hz	
Power Consumptions	Maximum (Scanning)	37 W	38 W	50 W	50 W
	Minimum (Standby)	17 W	19 W	17 W	19 W
	Sleep Mode	6 W	8 W	3.5 W	6 W
Environment	Operating Temperature and Humidity	Temperature 59°F to 86°F (15°C to 30°C) Humidity: 30% to 80% RH			
	Storage Temperature and Humidity	Temperature 59°F to 95°F (15°C to 35°C) Humidity: 10% to 80% RH			
Daily Duty Cycle	4,000 pages				
Additional Features	End User Replaceable Feeder Rollers, Electronic Color Dropout (Red, Green, Blue)				
Additional Contents	Power Cord, USB Cable, Roller Cleaning Paper, CD-ROM (Installation and Operation Manual, VRS, User Utility Software), Printed Documents (Quick Installation Guide and Warranty Card)				
Bundled Software	QuickScanPro Demo				
Consumables Options	Roller Exchange Kit S005503 Roller Cleaning Kit S005504		Roller Exchange Kit S005503 Roller Cleaning Kit S005504 Pre-scan Front-page Imprinter Kit 0123085 Ink Cartridge S005506		

© 2009 BÖWE BELL+HOWELL. All rights reserved. BÖWE BELL+HOWELL and the Böwe Bell+Howell logo are trademarks or registered trademarks of BBH, Inc. VirtualReScan and the VRS logo are registered trademarks of Kofax Imaging Products, Inc. All other trademarks and service marks are the property of their respective owners. Specifications are subject to change without notice.

Phone: 1.800.SCAN.494 or 1.847.675.7600
www.bbhscanners.com Form #SD-193, S007799 rev. B, 02/09



BÖWE BELL+HOWELL Scanners. Always adding value.